

Application No: 10/666,861      Docket No.: Q137-US2

Page 2

**IN THE CLAIMS**

1. (previously presented) An electric storage battery, comprising:  
a case defining an interior volume; and  
an electrode assembly in the interior volume, the electrode assembly including  
an electrically conductive elongate pin, and  
first and second electrode strips wound around the pin,  
the first electrode strip being coupled to the pin; and  
an elongate mandrel fitted around the pin.
2. (previously presented) The battery of claim 1, wherein the pin extends from the interior volume through the case such that the pin is configured to function as a first battery terminal.
3. (previously presented) The battery of claim 1, wherein the mandrel is electrically coupled to the pin.
4. (previously presented) The battery of claim 1, wherein at least one weld directly connects the first electrode strip to the pin.
5. (previously presented) The battery of claim 1, wherein the pin consists of a PtIr alloy.
6. (previously presented) The battery of claim 1, further comprising:  
a first end cap mounted on the pin,  
the first end cap including an electrical insulator,  
the pin extending through the electrical insulator, and  
the pin being hermetically sealed to the electrical insulator.
7. (previously presented) The battery of claim 1, wherein the mandrel defines an elongate slot and the first electrode strip extends through the slot.

Application No: 10/666,861      Docket No.: Q137-US2

Page 3

8. (previously presented) The battery of claim 1, wherein a weld attaches the mandrel to the pin.

9. (previously presented) The battery of claim 1, wherein the mandrel includes titanium or an alloy of titanium.

10.-65. (canceled)

66. (currently amended) The battery of claim 1, wherein a crimp connects the mandrel ~~is crimped~~ to the pin.

67. (currently amended) The battery of ~~claim 20~~ claim 1, wherein the mandrel includes a tube.

68. (original) The battery of claim 67, wherein the pin is positioned in an interior of the tube.

69. (original) The battery of claim 1, wherein the mandrel has a c-shaped cross-section.

70. (original) The battery of claim 1, wherein a portion of the first electrode strip is positioned between the mandrel and the pin.

71. (original) The battery of claim 1, wherein the mandrel is fitted around the pin such that the first electrode strip and the second electrode strip are wound around the mandrel.